

# 研削砥石用 研磨材の粒度

粗粒の粒度分布

粒度 3段目	ふるい目開き (mm、 $\mu$ m)	ふるい	規格	粒度 (F) 8
	4.00	1段	100%通過	0
				10
	3.35			0
				12
	2.80	2段	一定量以下	20
				0
				14
8	2.36	3段	一定量以上	45
				20
				0
				16
10	2.00	4段	3段及び4段あわせて一定量以上	70
				45
				20
				0
				20
12	1.70	5段	通過量が最大3%	(3)
				70
				45
				20
				0
14	1.40			24
				(3)
				70
				45
				20
16	1.18			0
				30
				(3)
				70
				45
20	1.00			0
				36
				(3)
				70
				45
				0
				25
				(3)
				70
				0
24	710			45
				25
				46
				(3)
30	600	54		65
				45
				20
				0
36	500	0	60	(3)
				65
				45
				0
				70
				(3)
				65
				30
46	355	30	0	80
				(3)
				40
54	300	40	30	0
				90
				65
60	250	65	40	25
				0
				100
				(3)
70	212	(3)	65	40
				25
				0
				120
80	180	(3)	65	40
				20
				0
				150
90	150		(3)	65
				40
				20
				0
				180
100	125		(3)	65
				40
				20
				0
				220
12	106		(3)	65
				40
				15
				0
				65
				15
150	75		(3)	65
				40
				15
180	63			(3)
				65
				40
220	53			(3)
				65
				40
				60