

## KM91028NFMA-A

- |  |  |
|--|--|
| 1. Material                                    | GaAlAs                                       |
| 2. Electrode                                   | N (cathode) side : Au<br>P (anode) side : Au |
| 3. Electrode pattern                           | Fig.1  |
| 4. Chip size                                   | 0.265 mm × 0.265 mm × 0.175 mm (Fig.1)       |
| 5. Emission area                               | 0.230mm X 0.230mm (Fig.1)                    |
| 6. Electro-Optical characteristics (Ta = 25°C) |  |

Parameters	Symbol	Condition	Min	Typ	Max	Unit
Power	Po	IF=20mA	2.0	4.3	-	mW
Forward Voltage	VF	IF=20mA	-	1.37	1.41	V
Reverse Current	IR	VR=3V	-	-	10	uA
Peak Wavelength	$\lambda_p$	IF=20mA	900	910	915	nm
Spectral Radiation Bandwidth	$\Delta\lambda(*)$	IF=20mA	-	45	-	nm

\* (\*) mark is reference data

\* Power Measurement at Resonac Photonics.

7. Recommended bonding method    Ultra-sonic method or a combination of ultra-sonic and thermo-compression methods.




Fig.1 : Chip size and Emission area and Electrode pattern

The information contained herein is believed to be reliable. However, no representations, guaranties or warranties of any kind are made as to accuracy and suitability of the Product for particular applications or the results of its use. Resonac Photonics Corporation reserves the right to introduce changes without notice.